

Aurum[®]

Gun Metal Angle Check Globe Valve Screwed Ends

Cat. No.: AU-AW24

Test Pressure Hydraulic

Body & Seat : 300psi

Temp. Range : 10°C to 225°C

SALIENT FEATURES :

- ✓ Screwed Female Ends to IS 554 BSP.
- ✓ Smooth Handwheel operation.
- ✓ Outlet at right angle.
- ✓ Rising Stem & Screwed-in Bonnet.
- ✓ Trouble free performance.
- ✓ Size Range from 15mm to 50mm.

UTILITY

WATER	AIR	STEAM	OIL	GASES
✓	□	□	✓	□

DIMENSIONS

Inches	mm	A	B	C
1/2	15	32	86	63
3/4	20	35	92	66
1	25	40	97	66
1¼	32	47	116	76
1½	40	54	130	90
2	50	64	147	90

MATERIAL :

Description	Material	Specifications
Set Screw	M.S.	IS : 1367
Washer	M.S.	IS : 226
Handwheel	C.I.	IS : 210 Gr. FG200
Stem	Brass	IS:6912 Gr. Flb
Gland, Gland Nut	Bronze	LTB2 of IS:318
Bonnet	Bronze	LTB2 of IS:318
Body	Bronze	LTB2 of IS:318
Disc Nut, Disc	Bronze	LTB2 of IS:318
Gland Packing	Asbestos	IS:4687

