

# Aurum<sup>®</sup>

## Gun Metal Globe Valve Flanged Ends

Cat. No.: AU-WF04

Test Pressure Hydraulic

Body: 1.5 Mpa      Seat: 1.0 Mpa

Temp. Range : 10°C to 225°C

### SALIENT FEATURES :

- ✓ Flanged Ends to IS 778.
- ✓ Smooth Handwheel operation.
- ✓ Strictly conforming to IS:778 Class I.
- ✓ Rising Stem & Screwed-in Bonnet.
- ✓ Trouble free performance.
- ✓ Back Seat Arrangement.
- ✓ Size Range from 15mm to 100mm.

IS:778



Marked



### UTILITY

WATER	AIR	STEAM	OIL	GASES
✓	□	□	✓	□

### DIMENSIONS

Inches	mm	A	B	C	D
1/2	15	75	87	59	95
3/4	20	85	92	59	105
1	25	95	97	68	115
1 1/4	32	110	116	83	140
1 1/2	40	120	131	91	150
2	50	145	144	99	165
2 1/2	65	165	165	108	185
3	80	185	186	126	200
4	100	216	203	161	220

### MATERIAL :

Description	Material	Specifications
Screw	M.S.	IS : 1367
Washer	M.S.	IS : 226
Handwheel	C.I.	IS : 210 Gr. FG200
Stem	Forged Brass	IS : 6912 Gr. FLB
Gland	Leaded Tin Bronze	IS : 318 Gr. LTB2
Gland Nut	Leaded Tin Bronze	IS : 318 Gr. LTB2
Bonnet, Body	Leaded Tin Bronze	IS : 318 Gr. LTB2
Disc Nut Disc	Leaded Tin Bronze	IS : 318 Gr. LTB2
Packing	Asbestos	IS:4687

